

Colored GS coat rack



GS coat rack supply.

Reference: 211.02 of the company Suffixe (70190 Rioz, phone: 03 84 91 24 70).

Quantity and dimension:

In function of the architect drawings

Technical description:

Double steel hook, of 6 mm diameter in cold forged. It is gathered on a frieze steel with a high rigidity, build as a U part (dimension : 15x35x2,5 mm covered by 100% polyester resin oven baked.)

Double frieze ivory-colored hook (RAL 9001).

Wall fixing thanks to a support (in S shaped). Invisible fastenings.

Double hook size: 95x45x30 mm

GS double hook distance between the two axles: 150 mm

Length from 60 cm to 3m, by slices of 15 cm.

General Information:

The color are set in function of the architect choice, following Suffixe double hook GS color chart.

Options:

The GS frieze coat rack is set up on a 10 mm grade laminate panel thickness. (ref. 211.12.) Panel dimension: overall length + 10 cm (195 cm max) – 12 cm width

Colors chosen by the architect following Suffixe grade laminate color chart (a total of 20 colors)



GS galvanized coat rack



Frieze GS galvanized coat rack supply.

Reference: 211.01 of the company Suffixe (70190 Rioz, phone: 03 84 91 24 70).

Quantity and dimension:

In function of the architect drawings.

Technical description:

Double hook size: 95x45x30 mm

GS Double hook distance between the 2 axles: 150 mm

Length from 60 cm to 3m, by slices of 15 cm.

Double steel hook build in 6 mm diameter, in cold forged and gathered on a frieze steel with a high ridigity build as a U part. (dimension 15x35x2,5 mm covered by 100% of polyester resin oven-baked.)

Galvanized double hook on a gray frieze (RAL 7040)

Wall fixing thanks to a support (in S shaped). Invisible fastenings.

Options:

The GS frieze galvanized coat rack is set on a 10 mm grade laminate panel thickness (ref. 211.11).

Panel dimension: overall length + 10 cm (195 cm max) – 12 cm width

Colors in function of the architect choice, following Suffixe grade laminate color chart (choice of 20 colors)